Technical Data Sheet

Design flooring 555 Wooden Styles Herringbone

Adhesive-type design floor covering



Article number(s):	6701 | 6702 | 6703 | 6704 | 6705 | 6706

Material / structure	
Structure	Core material: Heterogeneous PVC
Surface appearance	Wide range of wood looks with chamfered edges
Surface treatment	PU coating with synchronous pore
Installation possibilities	Full-surface adhesion

04|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Design flooring 555 Wooden Styles Herringbone

Dimensions and tolerance values in accordance with DIN EN ISO 10582. Dimension characteristics and permissible deviations in dimensions specified in the factory have been given in accordance with the type of elements for elastic floor coverings.

Dimensions of the individual element

Dimension	Tolerances
Thickness: 2.5 mm	
Length: 762.0 mm	
Width: 152.4 mm	
Thickness of the wear layer 0.55 mm	
Permissible deviation in width	≤ 0.10 % up to maximum 0.5 mm
Permissible deviation in perpendicularity	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in straightness	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in length	≤ 0.15 % up to maximum 0.5 mm
Permissible deviation in thickness of the element	± 0.15 mm
Change in dimension following effect of heat	≤ 0.25 %
Warping following effect of heat	≤ 2.0 mm

Product characteristics

Performance class	23/33/42
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Electrostatic behaviour when walked on	< 2 kV
Colour fastness	≥ Level 6
Castor chair test	Suitable chair caster type W
Residual indentation behaviour	≤ 0.1 mm
Chemical resistance	Resistant*
Thermal resistance	0.02 (m² x K) / W suitable for hot water underfloor heating
Degree of impact noise enhancement	approx. 2 dB
Pentachlorophenol content	Below the limit of what is technically measurable
Formaldehyde emission	E1
Weight per unit area	4,520 g/m²
Phthalate content	Phthalate-free

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume
INKU

Technical Data Sheet

Design flooring 555 Wooden Styles Herringbone

Adhesive recommendation

Manufacturer	Adhesive	Toothing	Consumption
JOKA	JK26	TKB A2	approx. 320 g/m²
Mapei	Ultrabond ECO 4 LVT	TKB A1 / A2	approx. 250 - 350 g/m²
Schönox	Durocoll	TKB A1 / A2	approx. 250 - 300 g/m²
Uzin	KE66	TKB A1 / A2	approx. 250 - 300 g/m²

Packaging

Contents per package 52-type	3.484 m²
Contents per pallet 52-type	250.838 m²
Number of elements per package 52-type	30
Packages per pallet 52-type	72

General product data

DoP number	LVTDESIGNF

All samples, brochures and photos are only provided in order to give you rough idea and are not binding. Both age and exposure to sunlight have an impact on the natural changes in colour of printed finishes. The colours of the original may vary from the way they look in print media or on a screen. At the time of delivery, the product may therefore show clear differences from the material sample provided. Only the technical data sheet, which you can find at www.jordanshop.de, is relevant with regard to specific product properties.



04|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU