Technical Data Sheet

Design flooring **555 XXL**

Adhesive-type design floor in XXL format



Article number(s):	9631 | 9632 | 9633 | 9634 | 9635

Material / Construction	
Structure	Core material: Heterogeneous PVC
Surface appearance	Wide range of wood looks with chamfered edges
Surface treatment	PU coating
Installation possibilities	Full-surface adhesion

11|2024

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Design flooring **555 XXL**

Dimensions and tolerance values are according to the DIN EN ISO 10582 norms. Dimension characteristics and permissible deviations in dimensions specified in the factory been given in accordance with the type of elements for elastic floor coverings.

Dimensions of the individual element

Dimension	Tolerances
Thickness: **2.5 mm**	
Length: **1,800 mm**	
Width: **228.6 mm**	
Thickness of the wear layer **0.55 mm**	
Permissible deviation in width	≤ 0.10 % up to maximum 0.5 mm
Permissible deviation in perpendicularity	≤ 0.25 mm
Permissible deviation in straightness	≤ 0.35 mm
Permissible deviation in length	≤ 0.15 % up to maximum 0.5 mm
Permissible deviation in thickness of the element	± 0.15 mm
Change in dimension following effect of heat	≤ 0.25 %
Warping following effect of heat	≤ 2.0 mm

Product characteristic

Performance class	33 / 42
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Electrostatic behaviour when walked on	≤ 2 kV
Colour fastness	≥ Grade 6 with artificial light
Castor chair test	Suitable chair caster type W
Residual indentation behaviour	≤ 0.1 mm
Chemical resistance	Resistant*
Thermal resistance	0.025 m² x K / W suitable for hot water underfloor heating
Degree of impact noise enhancement	approx. 4 dB
REACH Ordinance No. 1907/2206	Contains no materials named in the SVHC list
Weight per unit area	4,266 g/m²
Binding agent content	> 80 %
Phthalate content	Phthalate-free

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Design flooring **555 XXL**

Packaging	
Contents (area) per pack	4.41 m²
Contents per pallet	263.04 m²
Number of elements per pack	10
Packs per pallet	64 pieces

General product data	
DoP number	LVTDESXXL3

Note:
All samples, brochures and photos are only provided in order to give you a rough idea and are not binding.
Both age and exposure to sunlight have an impact on the natural changes in colour of printed finishes. The colours of the original may vary from the way they look in print media or on a screen.
At the time of delivery, the product may therefore show clear differences from the material sample provided.



Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at