Technical Data Sheet

Designböden **340 Click**

Click-type design floor covering



Article number(s):	812 | 823 | 824 | 833 | 834 | 835
	840 | 849 | 853 | 854 | 855 | 870
	871 | 874 | 876 | 880 | 882

Material / structure	
Structure	Transparent wear layer incl. PU coating Photo film Core material: 4.0 mm SPC (Rigid Board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Wide range of wood looks with all-round micro-chamfer
Surface treatment	PU coating
Connection system	ProConnect
Installation possibilities	Floating installation

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Designböden **340 Click**

Click-type design floor covering



Article number(s):	845 | 865 | 867 | 884 | 885

Material / structure	
Structure	Transparent wear layer incl. PU coating Photo film Core material: 4.0 mm SPC (Rigid Board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Range of stone looks with all-round micro-chamfer
Surface treatment	PU coating
Connection system	ProConnect
Installation possibilities	Floating installation

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Designböden **340 Click**

Dimensions and tolerance values in accordance with DIN EN ISO 10582. Dimension characteristics and permissible deviations in dimensions specified in the factory have been given in accordance with the type of elements for elastic floor coverings.

Dimensions of the individual element

Dimension	Tolerances
Thickness: **5.0 mm**	
Length: **1,244.6 mm / 607.2 mm**	
Width: **178.1 mm / 303.1 mm**	
Thickness of the wear layer **0.40 mm**	
Permissible deviation in width	≤ 0.10 % up to maximum 0.5 mm
Permissible deviation in perpendicularity	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in straightness	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in length	≤ 0.15 % up to maximum 0.5 mm
Permissible deviation in thickness of the element	± 0.15 mm
Change in dimension following effect of heat	≤ 0.15 %
Warping following effect of heat	≤ 1.0 mm

Product characteristics

Performance class	23/32
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Electrostatic behaviour	≤ 2 kV
Colour fastness	> Level 6
Castor chair test	Suitable chair caster type W
Residual indentation behaviour	≤ 0.10 mm
Chemical resistance	Resistant*
Thermal resistance	0.036 (m² x K) / W suitable for hot water underfloor heating
Pentachlorophenol content	Below the detection limit
Formaldehyde content	Not contained
Phthalate content	Phthalate-free
Weight per unit area	9,036 g/m²
Degree of impact noise enhancement	approx. 21 dB

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de

JOKA® Natürlich schöne Räume
INKU


Technical Data Sheet

Designböden **340 Click**

Packaging	
Contents (area) per pack	1.77 m² / 1.84 m²
Contents per pallet	106.2 m² / 117.76 m²
Number of elements per pack	8 / 10
Packs per pallet	60 / 64

General product data	
DoP number	LVTDESC4

Note:
All samples, brochures and photos are only provided in order to give you a rough idea and are not binding.
Both age and exposure to sunlight have an impact on the natural changes in colour of printed finishes. The colours of the original may vary from the way they look in print media or on a screen.
At the time of delivery, the product may therefore show clear differences from the material sample provided.



Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de

JOKA® Natürlich schöne Räume

INKU