Technical Data Sheet

Designböden **555 Click**

Click-type design floor covering



Article number(s):	207 | 208 | 209
	407 | 412 | 414 | 425
	509 | 529 | 540 | 541

Material / Construction	
Structure	Transparent wear layer incl. PU coating Photo film Core material: 5.0 mm SPC (Rigid Board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Wide range of wood looks with chamfered edges
Surface treatment	PU coating
Connection system	Pro Connect - installation system
Installation options	Floating installation

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical Data Sheet

Designböden **555 Click**

Click-type design floor covering



Article number(s):	542
	606 | 607 | 609

Material / Construction	
Structure	Transparent wear layer incl. PU coating Photo film Core material: 5.0 mm SPC (Rigid Board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Range of stone looks with chamfered edges
Surface treatment	PU coating
Connection system	Pro Connect - installation system
Installation options	Floating installation

04|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical Data Sheet

Designböden **555 Click**

Dimensions and tolerance values are according to the DIN EN ISO 10582 norms. Dimension characteristics and permissible deviations in dimensions specified in the factory been given in accordance with the type of elements for elastic floor coverings.

Dimensions of the individual element

Dimension	Tolerances
Thickness: **6.0 mm**	
Length: **1,212.8 mm / 91.44 mm**	
Width: **177.8 mm / 45.72 mm**	
Thickness of the wear layer **0.55 mm**	
Permissible deviation in width	≤ 0.10 % up to maximum 0.5 mm
Permissible deviation in perpendicularity	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in straightness	≤ 400 mm ≤ 0.25 mm > 400 mm ≤ 0.35 mm
Permissible deviation in length	≤ 0.15 % up to maximum 0.5 mm
Permissible deviation in thickness of the element	± 0.15 mm
Change in dimension following effect of heat	≤ 0.15 %
Warping following effect of heat	≤ 1.0 mm

Product characteristics

Performance class	23/33
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Electrostatic behaviour	≤ 2 kV
Colour fastness	> Level 6
Castor chair test	Suitable chair caster type W
Residual indentation behaviour	< 0.1 mm
Chemical resistance	Resistant*
Thermal resistance	0.049 (m² x K) / W suitable for hot water underfloor heating
Pentachlorophenol content	Not detectable
Formaldehyde content	E1
Phthalate content	Phthalate-free
Weight per unit area	9,500 g/m²
Impact noise enhancement	approx. 21 dB

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

04|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Designböden **555 Click**

Packaging	
Contents (area) per pack	1.73 m² / 2.09 m²
Contents per pallet	86.50 m² / 83.60 m²
Number of elements per pack	8 / 5
Packages per pallet	50 / 40

General product data	
DoP number	LVTDESCLIC

All samples, brochures and photos are therefore only provided in order to give you a rough idea and are not binding. Both age and exposure to sunlight have an impact on the natural changes in colour of printed finishes. The colours of the original may vary from the way they look in print media or on a screen. At the time of delivery, the product may therefore show clear differences from the material sample provided. Only the technical data sheet, which you can find at www.jordanshop.de, is relevant with regard to specific product properties.



04|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at