Technical Data Sheet

Design flooring **555 Evolut Herringbone Click**

Click-type design floor covering

Material / Construction	
Structure	Transparent wear layer incl. PU coating Photo film Core material: 5.0 mm SPC (Rigid Board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Wide range of wood & stone looks with chamfered edges
Surface treatment	EIR ≙ PU coating with synchronous pores
	n-EIR ≙ PU coating without synchronous pores
Connection system	UNIZIP
Installation options	Floating installation

Dimensions and tolerances in accordance with EN 16511.

Dimensions of the individual element	
Dimension	**Tolerances**
Thickness: **6.0 mm**	
Length: **630.0 mm**	
Width: **126.0 mm**	
Thickness of the wear layer **0.55 mm**	
Permissible deviation in width	≤ 0.10 mm, relative to the nominal value
Permissible deviation in perpendicularity	≤ 0.20 mm
Permissible deviation in straightness	≤ 0.30 mm
Permissible deviation in length	> 1,500 mm: Δ ≤ 0.3 mm/m
Permissible deviation in thickness of the element	on average ≤ 0.50 mm / t_{max} - t_{min} ≤ 0.80 mm
height differences between joined elements	Δ ≤ 0.10 mm max ≤ 0.15 mm
Joint opening between joined elements	Δ ≤ 0.15 mm / max ≤ 0.20 mm
Flatness of the element	concave width: ≤ 0.15 % convex: ≤ 0.20 % concave length: ≤ 0.50 % convex: 1.00 %

05|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU

Technical Data Sheet

Design flooring **555 Evolut Herringbone Click**

Product characteristic

Performance class	23/33
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Lightfastness	≥ Level 6
Castor chair test	Suitable chair caster type W
Residual indentation behaviour	≤ 0.2 mm
Chemical resistance	Resistant*
Thermal resistance	0.035 (m² x K) / W suitable for hot water underfloor heating
Formaldehyde content	E1
Weight per unit area	approx. 8,866 g/m²
Impact noise enhancement	approx. 21 dB

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

Packaging

Contents (area) per pack	0.794 m²
Contents per pallet	85.75 m²
Number of elements per pack	10
Packs per pallet	108

General product data

DoP number	LVTDESIGNJ

All samples, brochures and photos are therefore only provided in order to give you a rough idea and are not binding. Both age and exposure to sunlight have an impact on the natural changes in colour of printed finishes. The colours of the original may vary from the way they look in print media or on a screen. At the time of delivery, the product may therefore show clear differences from the material sample provided. Only the technical data sheet, which you can find at www.jordanshop.de, is relevant with regard to specific product properties.

Pictograms / Quality seal / Certificates



05|2025

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA® Natürlich schöne Räume

INKU