Technical data sheet

Homeline LVT 30 Click

Click-type design floor covering



Article number(s):	31-04 | 31-06 | 31-15 |31-19
	31-20 | 31-21 | 31-22 | 31-23

Material / Construction

Structure	Transparent wear layer incl. PU coating Photographic film Core material: 3.8 mm SPC (rigid board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Wide range of wood looks, chamfered on all four sides
Surface treatment	PUR coating
Connection system	ProConnect
Installation options	Floating installation

Information subject to technical modifications and error. All previous data sheets are no longer valid on publication of this edition.

INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical data sheet

Homeline LVT 30 Click

Click-type design floor covering



Article number(s):	31-12 | 31-24

Material / Construction

Structure	Transparent wear layer incl. PU coating Photographic film Core material: 3.8 mm SPC (rigid board) Integrated impact sound insulation IXPE: 1.0 mm
Surface appearance	Range of stone optics, chamfered on all four sides
Surface treatment	PUR coating
Connection system	ProConnect
Installation options	Floating installation

Information subject to technical modifications and error. All previous data sheets are no longer valid on publication of this edition.

INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical data sheet

Homeline LVT 30 Click

Dimensions and tolerance values are according to the DIN EN ISO 10582 norms. Dimension characteristics and permissible deviations in dimensions specified in the factory been given in accordance with the type of elements for elastic floor coverings.

Dimensions of the individual element

Dimension	**Tolerances**	
Thickness: **4.8 mm**		
Length : **1,244.6 / 607.2 mm**		
Width: **178.1 / 303.1 mm**		
Thickness of the wear layer: **0.30 mm**		
Permissible deviation in width	≤ 0.10 % up to maximum 0.5 mm	
Permissible deviation in perpendicularity	≤ 400 mm ≤ 0.25 mm	> 400 mm ≤ 0.35 mm
Permissible deviation in straightness	≤ 400 mm ≤ 0.25 mm	> 400 mm ≤ 0.35 mm
Permissible deviation in length	≤ 0.15 % up to maximum 0.5 mm	
Permissible deviation in thickness of the element	± 0.15 mm	
Change in dimension following effect of heat	≤ 0.25 %	
Warping following effect of heat	≤ 2.0 mm	

Product characteristic

Performance class	23/31
Fire behaviour	B_{fl} s1
Slip resistance	R10 / DS
Electrostatic behaviour when walked on	< 2 kV
Colour fastness	≥ Level 6 with artificial light
Castor chair test	Suitable, chair caster type W
Residual indentation behaviour	≤ 0.1 mm
Chemical resistance	Resistant*
Thermal conductivity	0.145 W/m x K suitable for hot water underfloor heating
Thermal resistance	0.028 m² x K/W suitable for hot water underfloor heating
Weight per unit area	7,850 g/m²
Impact noise enhancement	21 dB

*Resistance depends on concentration and exposure time. In the event of increased exposure to oils, greases, acids, lyes and other aggressive chemicals, the manufacturer must be consulted.

Information subject to technical modifications and error. All previous data sheets are no longer valid on publication of this edition.

INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical data sheet

Homeline LVT 30 Click

Packaging	
Contents (area) per pack	1.773 m² / 1.84 m²
Contents per pallet	106.20 m² / 125.1 m²
Number of elements per pack	8 / 10
Packs per pallet	60 / 68

General product data	
DoP number	PVCHOME30C



Information subject to technical modifications and error. All previous data sheets are no longer valid on publication of this edition.

INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at