


Technical Data Sheet

Laminate Flooring

633 Hudson River Tiles

Laminate floor tile board



Article number(s):	6725 6726 6727 6728

Material / Construction

Construction of an element	Surface layer: resistant overlay
	Central layer: QuellStop AQUAplus - coreboard
	Backing: moisture-inhibiting stabilising film
Surface appearance	Tile board, V4 chamfered
Surface treatment	Tile texture
Connection system	ProConnect Aqua Pure+ installation system
Laying options	Floating installation

Technical Data Sheet

Laminate Flooring

633 Hudson River Tiles

Dimensions and tolerances in accordance with EN 13329. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard for laminate floorings.

Dimensions of the individual element

Dimension	Tolerances
Thickness: 8.0 mm	
Length: 638.0 mm	
Width: 330.0 mm	
Permitted width deviation of the surface layer	≤ 0.10 mm, relative to nominal value
Permitted deviation of the squareness	≤ 0.20 mm
Permitted length deviation of the surface layer	≤ 0.30 mm/m, relative to the nominal value
Permitted deviation of the element thickness	≤ 0.50 mm, relative to the nominal value
Height difference between joined elements	≤ 0.15 mm
Joint opening between joined elements	≤ 0.20 mm
Straightness of the surface layer	≤ 0.30 mm/m
Flatness of the element	concave width: ≤ 0.15 % convex width: ≤ 0.20 % concave length: ≤ 0.50 % convex length: 1.00 %
Squareness	≤ 0.20 mm

Product characteristic

Use class	33
Reaction to fire	C _{fl} s1
Abrasion resistance	AC5
Impact resistance	small diameter ball ≥ 70 mm / large diameter ball ≥ 1000 mm
Resistance to staining	Group 1 & 2: Grade 5 / Group 3: \geq Grade 4
Residual impression	≤ 0.05 mm
Effect of a furniture leg	No damage shall be visible, when tested with foot type 0
Effect of a castor chair	suitable (chair castor type W)
Lightfastness	Blue wool scale ≥ 6 / Greyscale ≥ 4
Slip resistance	DS
Formaldehyde emission	E1
Thickness swelling	≤ 10.0 %
Thermal resistance	0.073 (m ² x K) / W suitable for hot water underfloor heating

Technical Data Sheet

Laminate Flooring

633 Hudson River Tiles

Packaging

Contents (area) per pack	2.316 m ²
Contents per pallet	74.11 m ²
Number of elements per pack	11
Packs per pallet	32

General product data

DoP number	PAR1702303-KR270
------------	------------------

Certificates



www.blauer-engel.de/uz176

