

# PRESTIGE

## PRODUCT DATASHEET 2018



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Ash Oak	(BHN) EN1534	4,0 3,7
Taber Abraser/Lacquer's wear resistance Proteco Hardwax Oil	EN 13696	N/A
Reduction of sound weighted index $\Delta L_w$ in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m <sup>2</sup> K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 14 mm	EN 12664 / EN 14342:2013	0,11

INSTALLATION		
Installation method	2-lock for floating or glue down	
Installation instruction	Download from <a href="http://www.tarkett.com">www.tarkett.com</a> Contact your supplier for more details	
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system		Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m²		

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil
See more alternatives and the complete range of accessories @ <a href="http://www.tarkett.com">www.tarkett.com</a>	

DIMENSIONS & PACKAGE	14x162x2200	14x190x2000
Thickness EN 13489 (mm)	14	14
Width (mm)	162	190
Length (mm)	2200	2000
Wear layer thickness (mm)	3,5	3,5
Boards/pack	6	6
m <sup>2</sup> /pack	2,14	2,28
m <sup>2</sup> /pallet	77,04	79,80
Net weight/m <sup>2</sup> (kg)	7,9	7,9

DIMENSIONS & PACKAGE	14x190x2200	14x194x2281
Thickness EN 13489 (mm)	14	14
Width (mm)	190	194
Length (mm)	2200	2281
Wear layer thickness (mm)	3,5	3,5
Boards/pack	6	6
m <sup>2</sup> /pack	2,51	2,66
m <sup>2</sup> /pallet	87,85	93,10
Net weight/m <sup>2</sup> (kg)	7,9	7,9

Due to the nature of the material this table shows typical values.

### MAINTENANCE

Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.

See maintenance instructions @ [www.tarkett.com](http://www.tarkett.com)

Prestige Proteco Hardwax Oil

TARKETT SUSTAINABILITY TAG	98 % 98 %	100 %
	Natural Renewable	Recyclable



# PRESTIGE

## DESIGN

A wooden floor that appears to be worn by the sun, wind and water. The boards have a new deep and rounded "Antique brushed" effect enhanced by a hardwax oil treatment, offering an easy and long-lasting maintenance. The 4-sided minibevels underline the character of the planks.

PRODUCT DATA	Material code	Size (mm)			Pattern	Surface treatment	Surface effect	Bevel (4 side)	Stained	DoP no.
		Thickness	Width	Length						
Prestige Ash Seashell	7967018	14	162	2 200	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Yes	0190-0105
Prestige Oak White Sand	7877046	14	190	2 200	1-strip		Antique brushed	Minibevel	Yes	0190-0105
	7877052	14	190	2 000	1-strip		Antique brushed	Minibevel	Yes	0190-0105
Prestige Oak Driftwood	7870059	14	194	2 281	3-strip		Antique brushed	-	Yes	0190-0105
Prestige Oak Sand	7870058	14	194	2 281	3-strip		Antique brushed	-	Yes	0190-0105
Prestige Oak	7877048	14	190	2 200	1-strip		Antique brushed	Minibevel	No	0190-0105
Prestige Oak Dark Slate	7877047	14	190	2 000	1-strip		Antique brushed	Minibevel	Yes	0190-0105



Prestige Ash Seashell



Prestige Oak White Sand



Prestige Oak Driftwood



Prestige Oak Sand



Prestige Oak



Prestige Oak Dark Slate

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or [www.tarkett.com](http://www.tarkett.com). Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit [www.tarkett.com](http://www.tarkett.com)