

iD CLICK ULTIMATE


TECHNICAL DATA

Certification & classification	Standards	iD Click Ultimate		
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering		
Classification	EN ISO 10874	Domestic: 23 Commercial: 34 Industrial: 43		
Technical characteristics				
Total thickness	EN ISO 24346	6,5 mm		
Wear layer thickness	EN ISO 24340	0,7 mm		
Total weight	EN ISO 23997	11,3 kg/m ²		
Wear layer binder content	EN ISO 10582	Type I		
Dimensions	EN ISO 24342	Planks	176 x 1213 mm	6 planks/box = 1,28 m ²
		Tiles	300 x 600 mm	7 tiles/box = 1,26 m ²
Surface treatment (PUR)		Yes - PUR Ultimate		
Beveled edges		Yes - 4 Bevels		
Technical performances				
Dimensional stability	EN ISO 23999	Average measured value 0,05% Required value ≤ 0.15%		
Curl resultant to heat	EN ISO 23999	≤ 1 mm		
Reaction to fire	EN 13501-1	B _n -s1		
Residual indentation	EN ISO 24343-1	≤ 0,05 mm		
Furniture leg	EN 424	No damage		
Castor chair	ISO 4918 - EN 425	No damage		
Impact sound reduction	EN ISO 717-2	ΔL _w up to 19 dB		
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)		
Thermal resistance	EN ISO 10456	0,05 m ² K/W		
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6		
Chemical resistance	EN ISO 26987	Very Good		
Slip resistance	DIN 51130	R9		
	EN 13893	μ ≥ 0,30		
Electrical properties	EN 1815	≤ 2 kV		
Peeling resistance	EN ISO 24345	≥ 50N / 50mm		
Underfloor heating		Suitable - max. 27 °C		

The above information is subject to modification for the benefit of further improvement. (01/18).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00



Produced under license from I4F
<https://i4f-patents.com>